






CHAIN COUPLING

SIZE	Torque	PITCH	BORE		ØA	ØB	D	E	G	L	COVER		weight Approx	
			MIN	MAX							OD	H		
3812	6112	99	9.525 (3/8")	8	16	45	25	24.0	30	4.9	64.9	59	61	0.4
4012	8312	217	12.70 (1/2")	9	22	61	35	33.1	36	7.4	79.4	75	75	1.1
4014	8314	295	12.70 (1/2")	9	28	69	43					84		1.4
4016	8316	385	12.70 (1/2")	13	32	77	50					92		2
5014	1014	560	15.875 (5/8")	13	35	86	53	41.0	45	9.7	99.7	101	85	2.7
5016	1016	735	15.875 (5/8")		40	96	60					111		3.3
5018	1018	930	15.875 (5/8")		45	107	70					122		4.2
6018	1218	1750	19.05 (3/4")	18	56	128	85	51.1	56	11.5	123.5	142	106	7.4
6022	1222	2370	19.05 (3/4")		71	152	110					167		11.3
8018	1618	3880	25.40 (1")	23	75	170	115	65.3	63	15.2	141.2	186	130	16
8022	1622	5580	25.40 (1")	28	90	203	140		71		157.2	220		25.5
10020	2020	8780	31.75 (1.25")	33	110	233	160	81.9	80	18.8	178.8	250	148	38.5
12018	2418	13200	38.10 (1.5")	43	115	256	170	102.7	90	22.7	202.7	307	181	47.3
12022	2422	17100	38.10 (1.5")	53	145	304	210		100		222.7	357		72.8
16018	3218	28600	50.80 (2")	58	155	341	224	131.7	112	30	254	406	250	110
16022	3222	41700	50.80 (2")	73	190	405	280		140		310	472		184
20018	4018	57000	63.50 (2.5")	85	205	426	294	160.6	241	37.5	519.5	496	280	317
20022	4022	71900	63.50 (2.5")	95	260	507	374					578		488
24022	-	129000	76.20 (3")	117	290	608	420	197.3	353	45	751	-	-	872
24026	-	157000	76.20 (3")	147	365	705	520					-	-	1277
32022	-	255000	101.60 (4")	197	400	806	570	263.0	400	60	860	-	-	1791
40020	-	494000	127 (5")	247	450	932	640	332.3	512	75.6	1100	-	-	2862
40024	-	602000	127 (5")	297	560	1093	800					-	-	4295
40028	-	717000	127 (5")	347	670	1255	960					-	-	6020



CHAIN COUPLING

CHAIN COUPLING COVER