





FLEXIBLE GEAR COUPLINGS


Coupling No.	Power at 100 RPM in KW	MAX. Torque in NM	HUB BORE			DIMENSION										APPROX WEIGHT IN KG.		Bolt Size & No. of Bolt
			FLEX		RIGID	ø A	øB	øB1	C	øF	G	H	L	M	Full Flex	Half Flex		
			MIN	MAX	MAX													
FGC 100	11.5	500	10	30	45	120	50	70	45	75	3	15	93	55	4	4	M10 X 6	
FGC 101	28.5	1000	20	40	55	170	65	85	55	110	5	17	115	65	10	10	M12 X 6	
FGC 102	51.5	2710	30	55	70	185	85	110	70	125	5	17	145	85	15	15	M12 X 6	
FGC 103	96.5	4900	40	70	85	220	105	130	85	150	5	20	175	105	25	26	M16 X 6	
FGC 104	150	9200	50	85	105	250	130	160	105	175	5	20	215	125	39	40	M16 X 8	
FGC 105	230	14300	60	105	120	290	155	185	110	200	10	25	230	140	59	60	M18 X 8	
FGC 106	390	21950	75	115	140	320	175	215	125	230	10	25	260	155	85	87	M18 X 8	
FGC 107	515	37250	90	130	160	350	205	240	140	260	10	25	290	175	111	112	M20 X 10	
FGC 108	644	49180	105	150	185	380	230	285	155	290	10	25	320	200	150	151	M20 X 12	
FGC 109	930	61500	125	165	205	430	250	315	165	330	10	25	340	210	210	220	M24 X 10	
FGC 110	1265	88800	140	200	240	490	310	370	180	390	10	25	370	230	300	310	M24 X 12	
FGC 111	1600	120800	160	230	260	545	350	380	200	445	10	30	410	270	440	450	M24 X 12	
FGC 112	2880	152800	180	260	280	590	400	420	240	490	10	30	490	300	630	650	M24 X 14	
FGC 113	3980	275000	200	300	340	680	440	480	260	555	15	35	535	320	870	895	M30 X 16	
FGC 114	4500	380000	220	350	365	730	500	520	280	610	15	35	575	340	1030	1050	M30 X 16	
FGC 115	4750	455000	250	380	400	780	540	560	320	660	15	35	655	385	1400	1380	M30 X 18	
FGC 116	6800	650000	260	440	460	900	625	650	350	755	20	45	720	425	2150	2090	M36 X 18	
FGC 117	9000	850000	375	505	530	1000	720	750	400	855	20	45	820	490	3100	2900	M36 X 20	
FGC 118	11800	1120000	450	570	580	1100	810	820	450	950	20	55	920	535	4000	4050	M36 X 20	
FGC 119	15500	1460000	520	640	650	1250	910	920	485	1050	30	55	1000	560	6200	5300	M48 X 20	




FGC 100-110



FGC 111 - 119



HGC 100 - 110



HGC 111 - 119