




PIN BUSH COUPLING

SIZE	No of Pins	Torque Nm	Max. RPM	BORE		ØA	ØB	C	L	M	G	Weight Approx
				MIN.	MAX.							
FPBC 1	3	75	6000	12.5	26	95	40	38	79	60	3	1.600
FPBC 2	4	300	5000	12.5	28	114	42	48	99	70	3	3.100
FPBC 2A	6	515	4300	16	40	130	60	51	105	70	3	4.500
FPBC 3	4	620	3500	16	45	160	68	51	107	115	5	8.800
FPBC 4	4	830	3000	20	60	191	90	60	125	115	5	14.200
FPBC 4A	6	1240	3000									13.800
FPBC 5	6	1660	2600	25	68	225	105	76	157	115	5	22.100
FPBC 6	8	2350	2250	45	90	254	135	89	183	115	5	33.300
FPBC 6A	10	2930	2250									32.900
FPBC 6B	12	3530	2250									32.600
FPBC 7	12	4150	1900	60	110	290	170	115	235	130	5	52.700
FPBC 7A	14	5190	1900	60	120	300	180	115	235	130	5	61.000
FPBC 8	16	5810	1800	60	130	310	195	125	255	140	5	72.500
FPBC 8A	18	7260	1700	65	135	340	200	130	265	150	5	83.400
FPBC 8B	12	8720	1590	70	140	360	210	135	276	170	6	106.300
FPBC 9	13	9930	1450	80	150	390	225	155	316	175	6	135.000
FPBC 9A	15	13270	1400	90	160	410	240	165	336	200	6	156.600
FPBC 10	16	14400	1300	100	170	440	255	180	366	220	6	188.400
FPBC 10A	17	18025	1200	110	180	480	270	190	386	225	6	227.500
FPBC 11	20	23700	1050	120	190	530	285	200	406	235	6	271.200



PIN BUSH COUPLING