



ROTEX TYPE COUPLING									
COUPLING SIZE	TORQUE NM	MAX.RP M	MAX. BORE/ D	A	B	L	L1	L2	G
FGR-19	18	14000	25	40	40	66	25	25	16
FGR-24	60	10500	32	55	55	78	30	30	18
FGR-28	165	8500	40	65	65	90	35	35	20
FGR-38	330	7000	48	80	79	114	45	45	24
FGR-38A						164	70	70	
FGR-42	475	6000	55	95	94	126	50	50	26
FGR-42A						176	75	75	
FGR-48	525	5600	62	105	104	140	56	56	28
FGR-48A						188	80	80	
FGR-55	690	4800	72	120	118	160	65	65	30
FGR-55A						210	90	90	
FGR-65	970	4250	80	135	133	185	75	75	35
FGR-65A						235	100	100	
FGR-75	1980	3550	95	160	158	210	85	85	40
FGR-75A						260	110	110	
FGR-90	3520	2800	110	200	198	245	100	100	45
FGR-90A						295	125	125	
FGR-100	4800	2500	130	225	220	270	110	110	50
FGR-100A						330	140	140	
FGR-110	7100	2000	150	255	250	295	120	120	55
FGR-110A						355	150	150	
FGR-125	9950	1600	170	290	285	340	140	140	60
FGR-125A						400	170	170	

