





TAPER GRID COUPLING

Size	Torque (nm)	Max. speed rpm	BORE		ØA		ØB	C	G	L	M	APPROX. WEIGHT KG.
			MIN	MAX	(T20) V. COVER	(T10) H. COVER						
1020	48	6000	13	26	111	101	40	47.5	3	98	62.5	2.0
1030	134	6000	13	32	121	110	50	47.5	3	98	62.5	2.6
1040	219	6000	13	38	128	117	57	51.0	3	105	66.0	3.4
1050	391	6000	13	42	147	138	67	60.5	3	124	75.5	5.4
1060	620	6000	18	50	162	150	76	63.5	3	130	78.5	7.3
1070	897	5500	18	56	173	162	87	76.0	3	155	91.0	10.4
1080	1860	4750	25	68	200	194	105	89.0	3	181	104.0	17.7
1090	3339	4000	25	80	232	213	124	98.5	3	200	113.5	25.4
1100	5676	3250	40	92	267	250	142	120.5	4.5	245.5	135.5	42.2
1110	8395	3000	40	105	286	270	160	127.0	4.5	258.5	142.0	54.4
1120	12401	2700	60	115	319	308	170	149.0	6	304	164.0	81.6
1130	18030	2400	65	140	378	346	217	162.0	6	330	177.0	122.5
1140	25948	2200	65	165	416	384	254	183.0	6	372	198.0	180.0
1150	36155	2000	100	175	476	453	269	183.0	6	372	198.0	230.0
1160	50810	1750	120	195	533	501	305	198.0	6	402	213.0	321.0
1170	67746	1600	130	230	584	566	355	216.0	6	438	231.0	448.0
1180	93941	1400	150	260	630	630	394	239.0	6	484	254.0	591.0
1190	124201	1300	150	285	685	675	437	260.0	6	526	275.0	761.0
1200	169365	1100	170	325	737	757	498	279.5	6	565	294.5	1021.0



T20



T10